AM/FM STEREO RECEIVER

SX-950

KCU

REV. BY	DATE	DESCRIPTION

REV. BY	DATE	DESCRIPTION

REV. BY	DATE	DESCRIPTION

PIONEER

SWITCHES :
- S_1 POWER OFF — ON
- S_2 RELAY OFF — ON
- S_{11} AM OFF — ON
- S_{12} FM OFF — ON
- S_{13} PHONO 1 OFF — ON
- S_{14} PHONO 2 / MIC OFF — ON
- S_{15} AUX OFF — ON
- S_{16} DUPLICATE OFF — ON
- S_{17} TAPE MONITOR 1 OFF — ON
- S_{18} TAPE MONITOR 2 OFF — ON
- S_{19} ADAPTOR OFF — ON
- S_{20} MODE STEREO — MONO
- S_{21} MUTING OFF — -20 dB
- S_{22} LOUDNESS OFF — ON
- S_{23} TURNOVER 400 — 200 Hz
- S_{24} TURNOVER 2.5K — 5 kHz
- S_{25} TONE OFF — ON
- S_{26} LOW FILTER OFF — 50 Hz
- S_{27} HIGH FILTER OFF — 6 kHz
- S_{28} SPEAKER A OFF — ON
- S_{29} SPEAKER B OFF — ON
- S_{30} SPEAKER C OFF — ON
- S_{31} MPX NOISE FILTER OFF — ON
- S_{32} FM MUTING ON — OFF
- S_{33} DE-EMPHASIS 25 μS — 75 μS

RESISTORS :
IN OHM, 1/4W, ± 5 % TORELANCE UNLESS OTHERWISE NOTED.
k : KΩ, M : MΩ

CAPACITORS :
IN μF UNLESS OTHERWISE NOTED P : pF

V : SIGNAL VOLTAGE NECESSARY FOR OBTAINING 85W/8Ω OUTPUT POWER (1kHz)
V : DC VOLTAGE AT NO INPUT SIGNAL
A : DC CURRENT AT NO INPUT SIGNAL
( )V : DC VOLTAGE AT 85W/8Ω OUTPUT (1k Hz)

TUNER Ass'y AWE - 066
AWS - 094 3/4
AWS - 094 1/4
AWS - 095 3/2
FM MUTING SWITCH Ass'y AWS - 093
DE-EMPHASIS SWITCH Ass'y AWX - 095
SP CONNECTOR Ass'y AWX - 062
LAMP Ass'y AWX - 036
POWER SUPPLY Ass'y AWR - 101
FUNCTION SWITCH Ass'y AWS - 094 1/4
AWS - 094 2/4
EQUALIZER AMP Ass'y AWF - 011
MIC JACK Ass'y AWX - 034
FLAT AMP Ass'y AWG - 038
TONE AMP Ass'y AWG - 039
POWER AMP Ass'y AWH - 050
PROTECTION Ass'y AWM - 062
SPEAKER SWITCH Ass'y AWS - 095 1/2